

Dikey Palet Çemberleme Makinesi (Yan Kaynaklı)

Automatic Pallet
Vertical Strapping
Machine (Side Welded)



TEKNİK ÖZELLİKLER

- Kullanılan çember tipi: Polypropylene(PP)
Polyester(PET)
- Çember genişliği: 8- 19 mm
- Çember kalınlığı: 0,50 - 1,0 mm
- Gerdirme kuvveti: 0 - 300 kg
- Kaynak şekli: Isı
- Atma hızı: 2,4 - 5,5 m/ sn
- Geri çekme hızı: 2,4 - 5,5 m/ sn
- Gerdirme hızı: 0,25 m/ sn
- Besleme gerilimi: 220/400 V Üç Faz
- Elektrik sarfiyatı: 1 Kw
- Çerçeve standart ölçüsü: 1200 x 1400 mm
- Çember bobini iç ölçüleri: 390/405 mm;
genişlik 150/190 mm

TECHNICAL DATAS

- Type of strap: Polypropylene(PP)
Polyester(PET)
- Straps Width: 8- 19 mm
- Strap thickness: 0,50 - 1,0 mm
- Strap tensioning: 0 - 300 kg
- Strap junction: through welding
- Throwing speed: 2,4 - 5,5 m/sec
- Recovery speed: 2,4 - 5,5 m/sec
- Tension speed: 0,25 m/sec
- Supply electric voltage: 220/400 V three-phase
- Installed electric power: 1 Kw
- Arch standard dimensions: 1200 x 1400 mm
- Core inside diameter : 390/405 mm;
width 150/190 mm

